

**Security level: B according to VDMA 24992 - Conditions May '95**

Suitable for the storage of:  
 office documents, office equipment


**Description**  
 Aue series - wall safe (to built-in).

**Body:** single-walled body (3 mm thick)  
**Door:** double-walled door construction (35 mm thick)  
**Locking:** 2-way locking system - incl. overlapping profile on the hinge side

**Standard option**  
**Lock:** high security key lock I class VdS with two keys (65 mm)  
**Hinges:** internal  
**Door opening angle:** 90°  
**Colour:** RAL 7035 (light grey)

Art. No.	Model	Outer dimensions*			Inner dimensions			Door light		Anchoring		Weight	Shelves	Files	Volume
		Height mm	Width mm	Depth mm	Height mm	Width mm	Depth mm	Height mm	Width mm	Bottom number	Backwall number	Kg	Number	Number	Liters
17000	Aue	110	240	110	88	223	72	88	165	-	-	4	-	-	1
17001	Aue	157	240	110	135	223	72	135	165	-	-	5	-	-	2
17002	Aue	230	240	110	208	223	72	208	165	-	-	7,5	-	-	3
17003	Aue	300	240	110	278	223	72	278	165	-	-	9	-	-	4
17004	Aue	230	240	200	208	223	162	208	165	-	-	10	-	-	7
17005	Aue	300	240	200	278	223	162	278	165	-	-	12,5	-	-	10

\* excluding hinges, handles and fittings



**Closure options**

Standard option

Options available against surcharge



Key lock



Electronic lock (Excl. 17000-17001)



Euro Profile Lock



Preparation for Euro Profile Lock



All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.

