

# Model







### Security level: Class I according to EN 1143-1

Feature - The safes with hiding doors.

Suitable for the storage of:

- office documents, office equipment
- valuables
- gun

### Description

Dresden Lausa series - high security safes.

Body: multi-walled body (62 mm thick) **Door:** multi-walled door construction (104 mm thick) Locking: 4-way locking bolt system - incl. overlaping profile on the hinge side

### Standard option

Lock: high security key lock I class VdS with two keys

Boltwork handle: knob, protruding 12 mm

Hinges: internal

Mounting holes: 1 hole in the floor Colour: RAL 7035 (light grey)














## Model Dresden Lausa

Art. No.	Model	Oute	Outer dimensions*		Inner dimensions			Door light		Anchoring		Weight	Shelves	Files	Volume
		Height mm	Width mm	Depth mm	Height mm	Width mm	Depth mm	Height mm	Width mm	Bottom number	Backwall number	Kg	Number	Number	Liters
41200	Dresden Lausa	606	740	895	460	409	724	438	403	1	-	262	1	0	136
41201	Dresden Lausa	806	740	895	660	409	724	638	403	1	-	313	2	0	195
41202	Dresden Lausa	1006	740	895	860	409	724	838	403	1	-	359	2	0	255
41203	Dresden Lausa **	606	1260	860	460	736	694	438	738	1	-	367	1	0	235
41204	Dresden Lausa **	806	1260	860	660	736	694	638	738	1	-	436	2	0	337
41205	Dresden Lausa **	1006	1260	860	860	736	694	838	738	1	-	495	2	0	439





### Closure options

Standard option

Options available against surcharge













Electronic lock with mechanical

### Accessories available against surcharge








Inner safe with partition wall, 2 - door (Art. no. 41203-41205)





Extendable shelf Extendable drawer for







All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.