

## London-Heathrow





Security level: Class IV according to EN 1143-1 Fire rating: Fire-protected safes according to EN 15659 LFS 30 P

In order to save the fire-resistance certificate, the door should be built in the wall strictly according to the mounting manual instruction.




**Descritpion:** London-Heathrow series - strongroom door, burglar - proof.

**Door:** multi-walled door construction (130 mm thick) **Door frame:** double-walled (60 mm thick) **Locking:** 3-way locking bolt system - incl. overlaping profile on the hinge side

## Standard option:

Lock: high security key lock VdS II class with two keys (170 mm), one of them folding key and mechanical emergency lock VdS II class Boltwork handle: handle protruding 60 mm Hinges: external Door opening angle: 180° Mounting holes: 9 holes, 4 in each side and 1 in the top Colour: RAL 7035 (light grey)






Closure options

Standard option



Accessories available against surcharge





All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.

Strongroom doors

## Model London-Heathrow

Door light		Anchoring			Weight
		K			kg
Height mm	Width mm	Left Side number	Right Side number	In the top number	Kg
1594	742	4	4	1	633
1694	742	4	4	1	665
1894	842	4	4	1	783



Options available against surcharge



1echanical ode lock: Electronic lock



Additional keypad for inside lock



Alarm system elements, Alarm system



## Strongroom doors