



Security level: Class I according to EN 1143-1

Feature - The safes be approved and certified by IMP.

Suitable for the storage of:

- office documents, office equipment
- valuables

Description

Osnabrück series - high security safes.

Body: multi-walled body (35 mm thick)

Door: multi-walled door construction (83 mm thick)

Locking: 4-way locking bolt system - incl. overlapping profile on the hinge side

Standard option

Lock: high security key lock I class VdS with two keys (95 mm)

Boltwork handle: handle, protruding 60 mm

Hinges: external

Door opening angle: 180°

Mounting holes: 1 hole in the floor

Colour: RAL 7035 (light grey)

| Art. No. | Model | Outer dimensions* | | | Inner dimensions | | | Door light | | Anchoring | | Weight Kg | Shelves Number | Files Number | Volume Liters |
|----------|--------------|-------------------|-------------|-------------|------------------|-------------|-------------|--------------|-------------|------------------|--------------------|--------------|-------------------|-----------------|------------------|
| | | Height mm | Width mm | Depth mm | Height mm | Width mm | Depth mm | Height mm | Width mm | Bottom number | Backwall number | | | | |
| 40550 | Osnabrück | 355 | 530 | 415 | 270 | 450 | 292 | 255 | 430 | 1 | - | 57 | 1 | 3 | 35 |
| 40551 | Osnabrück | 455 | 455 | 415 | 370 | 375 | 292 | 355 | 355 | 1 | - | 60 | 1 | 5 | 40 |
| 40552 | Osnabrück | 770 | 530 | 415 | 685 | 450 | 292 | 670 | 430 | 1 | - | 95 | 1 | 12 | 90 |
| 40553 | Osnabrück | 1120 | 530 | 415 | 1035 | 450 | 292 | 1020 | 430 | 1 | - | 130 | 2 | 18 | 136 |
| 40554 | Osnabrück | 1470 | 530 | 415 | 1385 | 450 | 292 | 1370 | 430 | 1 | - | 170 | 3 | 24 | 182 |
| 40555 | Osnabrück | 1820 | 530 | 415 | 1735 | 450 | 292 | 1720 | 430 | 1 | - | 201 | 4 | 30 | 228 |
| 40556 | Osnabrück | 770 | 870 | 495 | 685 | 790 | 372 | 670 | 770 | 1 | - | 150 | 1 | 20 | 201 |
| 40557 | Osnabrück | 1120 | 870 | 495 | 1035 | 790 | 372 | 1020 | 770 | 1 | - | 200 | 2 | 30 | 304 |
| 40558 | Osnabrück | 1470 | 870 | 495 | 1385 | 790 | 372 | 1370 | 770 | 1 | - | 254 | 3 | 40 | 407 |
| 40559 | Osnabrück | 1820 | 870 | 495 | 1735 | 790 | 372 | 1720 | 770 | 1 | - | 304 | 4 | 50 | 510 |
| 40560 | Osnabrück ** | 1120 | 1230 | 495 | 1035 | 1150 | 372 | 1020 | 1130 | 1 | - | 275 | 2 | 45 | 443 |
| 40561 | Osnabrück ** | 1820 | 1230 | 495 | 1735 | 1150 | 372 | 1720 | 1130 | 1 | - | 411 | 4 | 75 | 742 |

* excluding hinges, handles and fittings ** 2-door




Body: multi-walled body 35 mm thick



Door: multi-walled door construction 83 mm thick

Closure options

Standard option




Key lock


Options available against surcharge



Mechanical code lock




Electronic lock




Electronic lock with mechanical emergency


Accessories available against surcharge




Inner safe (Excl. 40560-40561)




Inner safe with partition wall, 2 - door (Art. no. 40560-40561)




Shelf (Excl. 40550-40551)




Extendable shelf (Excl. 40550-40551)



Extendable drawer for individual arrangement (Excl. 40550-40551)



Shelf for hanging files (Excl. 40550-40551)



Extensible file frame (Excl. 40550-40551)



Alarm system elements/Alarm system (Excl. 40550-40551)



Left door



All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.