


# Model Rom-Lazio





In order to save the fire-resistance certificate, the door should be built in the wall strictly according to the mounting manual instruction.

Rom-Lazio series - strongroom door, burglar - proof.

**Door:** multi-walled door construction (130 mm thick) **Door frame:** double-walled (60 mm thick) Locking: 3-way locking bolt system - incl. overlaping profile on the hinge side

#### Standard option:

Lock: high security key lock class II VdS with two keys (170 mm)

Boltwork handle: handle, protruding 60 mm

Hinges: external

Door opening angle:  $180^{\circ}$ 

Mounting holes: 10 holes, 4 in each side and 2 in the

Colour: RAL 7035 (light grey)

### Descritpion:



Closure options



Standard option

VdS

Rom-Lazio

Rom-Lazio excluding hinges, handles and fittings

55400 55401

## Options available against surcharge

1694

1894

2000 1000 300

Door frame: double-walled (60 mm thick)

742

842



Model

Rom-Lazio

kg

#### Accessories available against surcharge







Door: multi-walled door construction (130 mm thick)









All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.

Strongroom doors **Strongroom doors**