

Model
save4ever I



Security level: Class I according to EN 1143-1

Suitable for the storage of:

- documents
- valuables

Description

Series **save4ever I** - high security safe - ECB•S certification.

Body: double-walled body (25 mm thick)
Door: multi-walled door construction (84 mm thick)
Locking: 4-way locking bolt system - incl. overlapping profile on the hinge side

Standard option

Lock: high security key lock I class VdS with three keys (95 mm)
Boltwork handle: handle, protruding 12 mm
Hinges: external
Door opening angle: 180°
Mounting holes: 1 hole in the floor, 1 on the backwall (not drilled) up to 1/3 height

Model
save4ever I

Art. No.	Model	Outer dimensions*			Inner dimensions			Door light		Anchoring		Weight Kg	Shelves Number	Files Number	Volume Liters	Hooks Number
		Height mm	Width mm	Depth mm	Height mm	Width mm	Depth mm	Height mm	Width mm	Bottom number	Backwall number					
402000.00	save4ever	400	400	270	350	341	157	288	304	1	1**	39	1	1	18	5***
402001.00	save4ever	400	420	420	350	361	307	288	324	1	1**	55	1	4	39	5***
402002.00	save4ever	500	500	420	450	441	307	388	404	1	1**	71	1	7	60	5***
402003.00	save4ever	650	500	420	600	441	307	538	404	1	1**	85	1	9	81	5***
402004.00	save4ever	800	500	420	750	441	307	688	404	1	1**	100	1	12	101	5***
402005.00	save4ever	1000	500	420	950	441	307	888	404	1	1**	120	2	15	127	5***
402006.00	save4ever	1150	500	420	1100	441	307	1038	404	1	1**	135	2	18	148	5***
402007.00	save4ever	1300	500	420	1250	441	307	1188	404	1	1**	150	3	20	168	5***

* excluding hinges, handles and fittings ** not drilled *** hook strip for self assembly



Body: double-walled body (25 mm thick)



Door: multi-walled door construction (84 mm thick)

Closure options

Standard option

Options available against surcharge




Key lock




Electronic lock Solar Basic




Mechanical code lock




Electronic lock Solar Business



Electronic lock Primor 3000 level 5



Electronic lock Primor 3000 level 15



Electronic lock B 30 (Excl. 402000.00 and 402001.00)



All information concerning weight, color and dimensions are noncommittal and subject to errors and changes. Minor deviations are conditional on the production process. Technical changes, modifications and printing errors reserved. Safes may be top-heavy, during commissioning, please exercise appropriate caution in accordance with the installation guide. Pictograms are not technical description of the product.